

Car parks

Reliable property protection and high closing speeds





Car parks



Individual solutions for the parking sector.



**High-speed spiral door
EFA-SST®**

Page 6



**High-speed spiral door
EFA-SST® PS**

Page 9



**High-speed spiral door
EFA-SST®**

Page 6



For more information about our solutions for the parking sector visit:
www.efaflex.com/car-parks



**High-speed folding door
EFA-SFT®**



EFA-SST®
AT A GLANCE:

- Max. heat insulation with EFA-THERM® laths
- Opening speed up to 2.5 m/s
- Closing speed up to 1.0 m/s
- Highest wind load capacity
- Top safety devices
- Up to 250,000 operating cycles p.a.
- Standard sizes up to w=10,000 mm, h=12,000 mm

Spiral door technology in perfection.

EFA-SST®

The EFA-SST® high-speed spiral door represents a new, more modern generation of industrial doors: perfect insulation, energy-efficient functionality, state-of-the-art technology. During the technical redesign, particular attention was paid to improving the physical properties of the door leaf as well as optimising the functionality, thus once again raising the standard of EFAFLEX industrial doors.

The pioneer in spiral technology. **EFA-SST® Classic**

Endlessly imitated – still unrivalled. The tried and tested basic concept for high-speed spiral doors from EFAFLEX remains unbeatable! The door leaf is not wound onto a shaft but rather kept at a distance in the EFAFLEX spiral to save space.

EFA-SST® CLASSIC AT A GLANCE:

- Aluminium laths double-walled
- Opening speed up to 2.0 m/s
- Closing speed up to 1.0 m/s
- Highest wind load capacity
- Top safety devices
- Up to 250,000 operating cycles p.a.
- Standard sizes up to
w=8,000 mm, h=7,000 mm



**EFA-SST® EFFICIENT
AT A GLANCE:**

- Slim frame for cramped installation locations
- Chain drive ensures minimal maintenance costs
- Resistance Class 2 in accordance with DIN/TS 18194:2020 – RC 2
- Opening and closing speed up to 0.5 m/s
- Up to 150,000 operating cycles p.a.
- Max. sizes
w=4,000 mm, h=5,130 mm
- Tested and certified by ift Rosenheim

The tailored safety solution.

EFA-SST® Efficient

Cramped installation situations require a custom-fit solution which can be integrated into the on-site conditions. With the EFA-SST® Efficient high-speed spiral door, EFAFLEX offers a compact and springless door which can also be positioned in locations with confined installation space. The scope of application for the EFA-SST® Efficient ranges from indoor use to use as a secure hall door. With an on-site canopy, the high-speed door can also be installed outdoors.





The fastest parking garage door in the world.

EFA-SST® PS

The EFA-SST® PS is a space-saving door specially developed for car park and garage systems and can be optimally installed even with minimal space in the lintel or side case area. In addition, it also features the typical properties of every EFAFLEX high-speed door: safe, reliable and incomparably fast.

EFA-SST® PS AT A GLANCE:

- Space-saving construction
- Opening speed up to 1.8 m/s
- Closing speed up to 1.0 m/s
- Highest wind load capacity
- Top safety devices
- Optionally with EFA-VENT® ventilation laths
- Up to 200,000 operating cycles p.a.
- Standard sizes up to
w=6,100 mm, h=4,000 mm



The folding door for outside and inside. **EFA-SFT®**

The EFA-SFT® combines functionality and aesthetics. Due to the modular structure, it is easy to repair and low-maintenance. Particularly large doors are fitted with special floor stoppers, to additionally stabilise the closed wing in the middle area. If necessary, the integration of pedestrian doors is also possible.

EFA-SFT® AT A GLANCE:

- Fast, robust, economical
- Minimal space requirement
- Excellent price-performance ratio
- Opening speed up to 2.5 m/s
- Closing speed up to 1.0 m/s
- Up to 150,000 operating cycles p.a.
- Standard sizes up to
w=5,250 mm, h=7,000 mm

Technical details

High-speed spiral doors

		Premium					ECO
Size		L	S	US	XL	XXL	L
Application	Interior door	●	●	●	●	●	●
	Lock-up doors	●	●	●	●	●	●
Wind load max.*	According to DIN EN 12424 class	2 - 4	2 - 4	2 - 4	0 - 2	2 - 4	2 - 4
Operating forces / safe closing	According to DIN EN 13241 class	fulfilled	fulfilled	fulfilled	erfüllt	fulfilled	fulfilled
Resistance against water ingress*	According to DIN EN 13241 class	3	3	3	3	1	3
Air permeability*	According to DIN EN 13241 class	3	3	3	3	3	3
Direct airborne sound insulation R _w *	in dB according to DIN EN 717-1	24	25	26	26	26	24
U value maximum*	in W/m ² K according to DIN EN 13241	1.52	0.91	0.66	0.66	0.54	1.52
Door size (in mm)	Width W max.	4,500	6,000	8,000	10,000	10,000	4,500
	Height H max.	5,000	6,000	8,000	6,600	12,000	5,000
Maximum door leaf speed*	in m/s	2.5	1.5	1.2	1.0	0.5	1.0
Guide of door leaf	Round Spiral	●	●	●	●	●	●
	Oval Spiral	●	●	-	-	-	●
	Low-header	-	-	-	-	-	●
Steel design	Galvanized sheet steel frame	●	●	●	●	●	●
	Stainless steel	○	○	-	-	-	○
	Powder coated in RAL colours	○	○	○	○	○	○
Door leaf	EFA-THERM® laths insulated/painted	●	●	●	●	●	●
	EFA-THERM® laths with double-walled viewing windows	-	-	-	-	-	-
	EFA-CLEAR® Vision laths double-walled, thermally separated	○	○	○	○	○	○
	EFA-CLEAR® Vision laths single-walled	○	○	-	-	-	○
	EFA-VENT® Ventilation laths	○	○	-	-	-	○
	EFA-ALUX® Aluminium laths	-	-	-	-	-	-
	Colour according to RAL (without vision panel)	○	○	○	○	○	○
Fire class	Building Material class DIN 4102	B2	B2	B2	B2	B2	B2
Weight balancing by		Spring	Spring	Spring	Spring	Spring	Spring
Designed for approx ... operating cycles per year		250,000	250,000	250,000	150,000	100,000	200,000
Drive	Electric motor	●	●	●	●	●	●
Control	EFA-TRONIC®	●	●	-	-	○	●
	EFA-TRONIC® Light	-	-	-	-	-	-
	EFA-TRONIC® Professional	○	○	●	●	●	○
	Main switch and foil keypad	●	●	●	●	●	●
Lead	Electricity connection 230 V/50 Hz	●	●	●	●	-	●
	Electricity connection 400 V/50 Hz	○	○	○	○	●	○
	Circuit breaker	16 A (K)	16 A (K)	16 A (K)	16 A (K)	16 A (K)	16 A (K)
Manual locking		●	●	●	●	●	○
Emergency operation	Automatic after manual activation	●	●	●	●	●	●
	Manual activation	-	-	-	-	-	-
Safety Devices	EFA-TLG® door light grid in door closing line	●	●	●	●	●	○
	Contact edge	○	○	-	-	-	●
	Light barrier	○	○	-	-	-	●
	Approach area monitoring	○	○	○	○	○	○
	Light grid, external	○	○	○	○	○	○
Safety system including activator	EFA-SCAN® frame/bollard	○/○	○/○	○/○	○/○	○/○	○/○
	LZR®-WIDESCAN	○	○	○	○	○	○

● Standard, ○ upon request, - Not available, npd = No Performance Determined *Depending on door leaf, guide of door leaf and door size, we reserve the right to make technical changes.

Technical details

High-speed spiral doors

		S Series			
		EFA-STT®			
Size		L	S	ÜS	L-N
Application	Interior door	●	●	●	●
	Lock-up doors	●	●	●	●
Wind load max.*	According to DIN EN 12424 class	3 – 4	2 – 4	2 – 4	3 – 4
Operating forces / safe closing	According to DIN EN 13241 class	fulfilled	fulfilled	fulfilled	fulfilled
Resistance against water ingress*	According to DIN EN 13241 class	0	0	0	0
Air permeability*	According to DIN EN 13241 class	2	2	2	0
Direct airborne sound insulation R _w *	in dB according to DIN EN 717-1	20	20	20	20
U value maximum*	in W/m²K according to DIN EN 13241	6.5	6.37	6.28	6.5
Door size (in mm)	Width W max.	4,000	6,000	8,000	4,000
	Height H max.	5,000	6,000	7,800	5,000
Maximum door leaf speed*	in m/s	3.0	2.8	2.0	1.8
Guide of door leaf	Round Spiral	●	●	●	–
	Low-header	–	–	–	●
Steel design	Galvanized sheet steel frame	●	●	●	●
	Stainless steel	○	○	–	○
	Powder coated in RAL colours	○	○	○	○
Door leaf	EFA-CLEAR® Vision laths single-walled	●	●	●	●
	EFA-VENT® Ventilation laths	○	○	○	○
	EFA-ALUX® Aluminium laths	–	–	–	○
	Vision panel single-walled / double-walled	●/–	●/–	●/–	●/–
	Non transparent infill single-walled / doublewalled	○/–	○/–	○/–	○/–
	Colour according to RAL (without vision panel)	○	○	○	○
Fire class	Building Material class DIN 4102	B2	B2	B2	B2
Weight balancing by		Spring	Spring	Spring	Spring
Designed for approx ... operating cycles per year		200,000	200,000	200,000	120,000
Drive	Electric motor	●	●	●	●
Control	EFA-TRONIC®	●	●	–	●
	EFA-TRONIC® Professional	○	○	●	○
	Main switch and foil keypad	●	●	●	●
Lead	Electricity connection 230 V/50 Hz	●	●	●	●
	Circuit breaker	16 A (K)	16 A (K)	16 A (K)	16 A (K)
Manual locking		○	○	○	○
Emergency operation	Automatic after manual activation	●	●	●	●
Safety Devices	EFA-TLG® door light grid in door closing line	○	*	*	○
	Contact edge	●	*	*	●
	Light barrier	●	*	*	●
	Approach area monitoring	○	○	○	○
	Light grid, external	○	○	○	○
	Safety system including activator	EFA-SCAN® frame/bollard	○/○	○/○	○/○
	LZR®-WIDESCAN	○	○	○	○

● Standard, ○ upon request, – Not available,

*Depending on door leaf, guide of door leaf and door size, we reserve the right to make technical alterations!

F Series

		EFA-SFT®			
		2-flg.	1-flg.	2-flg.	1-flg.
		L	L	S	S
	Size				
Application	Interior door Lock-up doors	○ ●	○ ●	○ ●	○ ●
Wind load max.*	According to DIN EN 12424 class	4	4	3	3
Operating forces / safe closing	According to DIN EN 13241 class	fulfilled	fulfilled	fulfilled	fulfilled
Resistance against water ingress*	According to DIN EN 13241 class	0	0	0	0
Air permeability*	According to DIN EN 13241 class	0	0	0	0
Direct airborne sound insulation R _w *	in dB according to DIN EN 717-1	21	21	21	21
U value maximum*	in W/m²K according to DIN EN 13241	4.88	4.88	4.66	4.66
Door size (in mm)	Width W max.	3,750	1,750	5,250	3,000
	Height H max.	3,750	3,750	7,000	7,000
Maximum door leaf speed*	in m/s	2.0	2.5	2.0	2.5
Steel design	Galvanized sheet steel frame	●	●	●	●
	Stainless steel	-	-	-	-
	Powder coated in RAL colours	○	○	○	○
Door leaf	EFA-THERM® laths insulated / painted	-	-	-	-
	Vision panel single-walled / double / triple	●/○/-	●/○/-	●/○/-	●/○/-
	non transparent infill single-walled / double	○/○	○/○	○/○	○/○
	Colour according to RAL (without vision panel)	○	○	○	○
	Door leaf modules made of anodized aluminium E6 / EV1	○	○	○	○
Fire class	Building Material class DIN 4102	B2	B2	B2	B2
Designed for approx ... operating cycles per year		150,000	150,000	150,000	150,000
Drive	Electric motor	●	●	●	●
Control	EFA-TRONIC®	●	●	●	●
	EFA-TRONIC® Light	-	-	-	-
	EFA-TRONIC® Professional	○	○	○	○
	Main switch and foil keypad	●	●	●	●
Lead	Electricity connection 230 V/50 Hz	●	●		

Telephone +49 8765 82-0

EFAFLEX® is a registered and legally protected trademark.

Subject to technical changes. Some diagrams depict special features.

Overall design:

www.creativconcept.de 12 | 2024

EFAFLEX 
safe high-speed doors