



Spiral design

- Very fast and quiet operation due to our spiral construction
- Designed to minimise contact, reducing abrasion to the door blade or curtain
- Round and low header versions available

Door blade

- Flexible door blade consists of individually changeable modular segments
- Fixed Aluminium profiles mounted every 225 mm reinforce the PVC curtain
- Several fabric colour options

Control EFA-TRONIC®

- Externally mounted polycarbonate control box
- With integrated frequency converter

Finish

- Galvanised, stainless steel or powder coating acc. to RAL

Safety

- Contact edge as a standard
- Optional infra-red light curtain (EFA-TLG)

Emergency operation

- Manual opening utilizing spring tension

Speed/Cycles

- Opening speed up to 4 m/s (depending on door size)
- 200,000 operating cycles per year

General

- Max. sizes
W = 7,000 mm x
H = 6,000 mm

(depending on width class 2.0)

-

EFA-STR®: Simply the fastest vertically opening door in the world

The EFA-STR® impresses with unbelievable speed, fantastic operating capacity, a light-weight practically wear-free door blade and good wind resistance. This flexible door is perfectly suited for internal and external applications.



Spiral design

- Very fast and quiet operation due to our spiral construction
- Designed to minimise contact, reducing abrasion to the door blade or curtain
- Round and low header versions available

Door blade

- Flexible door blade consists of individually changeable modular segments
- Fixed Aluminium profiles mounted every 225 mm reinforce the PVC curtain
- Several fabric colour options

Control EFA-TRONIC®

- Externally mounted polycarbonate control box
- With integrated frequency converter

Finish

- Galvanised, stainless steel or powder coating acc. to RAL

Safety

- Contact edge as a standard
- Optional infra-red light curtain (EFA-TLG)

Emergency operation

- Manual opening utilizing spring tension

Speed/Cycles

- Opening speed up to 4 m/s (depending on door size)
- 200,000 operating cycles per year

General

- Max. sizes
W = 7,000 mm x
H = 6,000 mm
- Wind class 2 – 3 (depending on door size)
- Tested and certified by ift institute