

## EFA-STT®: The transparent door with turbo speed

The EFA-STT's transparent door blade provides a clear view in both internal and external applications. Installed it creates a bright, comfortable and safe work environment. Its light-weight door blade enables amazing operating speeds, allowing accelerated logistics and manufacturing processes.



### Spiral design

- Extremely fast and quiet operation due to our spiral construction
- Designed to minimise contact, reducing abrasion to the door blade and glazing
- Round spiral and low header versions available

### Door blade

- Single-walled transparent laths available with acrylic or polycarbonate infills
- Optional grey infill and ventilation lath available

### Control EFA-TRONIC®

- Externally mounted polycarbonate control box
- With integrated frequency converter

### Finish

- Galvanised, stainless steel or powder coating acc. to RAL

### Safety

- Combined photo-cell and contact edge
- Optional infra-red light curtain (EFA-TLG')

### Emergency operation

- Manual opening utilizing spring tension

### Speed / Cycles

- Up to 3.0 m/s (depending on door size)
- 200.000 operating cycles per year

### General

- Max. sizes  
W = 8,000 mm x H = 7,800 mm
- Wind class 2 – 4  
(depending on door size)
- Tested and certified by ift institute

## EFA-STT®: The transparent door with turbo speed

The EFA-STT's transparent door blade provides a clear view in both internal and external applications. Installed it creates a bright, comfortable and safe work environment. Its light-weight door blade enables amazing operating speeds, allowing accelerated logistics and manufacturing processes.



### Spiral design

- Extremely fast and quiet operation due to our spiral construction
- Designed to minimise contact, reducing abrasion to the door blade and glazing
- Round spiral and low header versions available

### Door blade

- Single-walled transparent laths available with acrylic or polycarbonate infills
- Optional grey infill and ventilation lath available

### Control EFA-TRONIC®

- Externally mounted polycarbonate control box
- With integrated frequency converter

### Finish

- Galvanised, stainless steel or powder coating acc. to RAL

### Safety

- Combined photo-cell and contact edge
- Optional infra-red light curtain (EFA-TLG')

### Emergency operation

- Manual opening utilizing spring tension

### Speed / Cycles

- Up to 3.0 m/s (depending on door size)
- 200.000 operating cycles per year

### General

- Max. sizes  
W = 8,000 mm x H = 7,800 mm
- Wind class 2 – 4  
(depending on door size)
- Tested and certified by ift institute